



The enclosure protects the recorder against unauthorized access or theft. The enclosure is made of steel with a thickness of 1mm. It is equipped with lock and two tamper switches, indicating enclosure opening and detachment from the wall. Due to the vertical installation and low depth, it is ideal for places where deeper enclosures or cabinets type Rack19" cannot be installed. After opening the enclosure, the front cover is held in a horizontal position, providing easy access to the buttons on the front panel of DVR. The enclosure is fitted with a special adjustable handle for installation of recorders with the following dimensions: width from 145 mm to 345 mm, height: from 40 mm to 100 mm.

Dimensions:	internal: W=385, H=495, D=110 external: W=435, H=500, D=130[mm, +/-2]
The adjustment range	
of the mounting plate	
Max Width / Height:	from 145 mm to 345 mm / from 40 mm to 100 mm
Weight net/gross:	8,60kg / 9,00kg [+/-0,1kg]
Operating environment:	class II, -10°C÷ 40°C
Material description:	sheet steel DC01, thickness: 1,0mm, pcorrosion protection, color: RAL 9005 (black matt
Destination:	indoor
Tamper protection:	2 x microswitch: opening and detachment of the enclosure,
	0,5A@50V/DC max. NC- normally closed contacts
Closing:	lock
Notes:	distance from the wall 14mm
Declarations, warranty:	RoHS, 2 year from the production date