

KZ705

Kilsen KL700A Series Universal Fire Detector Base

General

The KZ705 is a 5 contact universal detector base for use with the KL700 and KL700A series detectors from Kilsen. In addition to the normal base and remote indication connectors, the KZ705 also has an additional earth terminal connector to allow for easy terminations of a possible cable screen. It allows for cable entry both from behind as well as from the side.

Installation Options

Even though the KZ705 supports surface mount options with cable entry from the side, situations may arise where conduit entry into the base is required. For such applications a surface mount accessory (S700) is optionally available.



Standard Features

- Universal base for both conventional and addressable detectors
- Additional screen/earth terminal available
- Remote indicator support
- Supports rear and side cable entry

KZ705

Kilsen KL700A Series Universal Fire Detector Base

Specifications

Dimensions (Ø x h)	100 x 29 mm
Weight	69 g
Operating voltage	
Current consumption	
Isolation current	
Isolation resistance	
Environmental characteristics	
Operating temperature	-10°C to 70°C
Storage temperature	-10°C to 70°C
Relative humidity (non-condensing)	10 to 95%

Ordering Information

Part No.	Description
KZ705	Kilsen KL700A Series Universal Fire Detector Base
PA25/3	
S700	Surface Mount Accessory for KZ700 and KZ705 Series Bases