

# TVB-5801

TruVision 2MPX, Stainless Steel, super low light, IP VF lens bullet camera, 3.8-16mm, True D/N, WDR, 50M IR, Micro SD/SDHC/SDXC slot, 24 VAC, IP67

## Overview

The TruVision Stainless Steel IP bullet camera leverages the latest H.265 video compression technology to bring state-of-the-art, high-definition pictures to the mass video surveillance market. With a resolution of 2 megapixels, this IP camera represents a flexible video surveillance device to meet the demanding requirements of marine and industrial requirements. Equipped with advanced technology and signal processing capability, they effectively capture video under challenging conditions.

TruVision cameras utilize H.264 and/or H.265 compression technology with triple-streaming capability, making it easy to manage the camera's bandwidth usage. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.

This camera has enhanced alarm capabilities, including cross lines, intrusion, de-focus and face detection features. Each is user-configurable to best suit the installation environment. A Region of Interest function ensures specific portions of an image are given priority during instances of high network traffic or network degradation.

Location-specific functions include a Hallway View Mode to provide a portrait view of a hallway or corridor, a De-Fog Mode to help resolve images through fog or rain and Electronic Image Stabilization for installations subject to physical vibration or shaking.



## Details

- Stainless Steel weather resistant construction for marine and industrial type environments
- Maximum Resolution: 1920 x 1080
- Maximum Real Time Resolution: 1920 x 1080 @ 25/30 fps (50/60 Hz)
- Designed to PSIA and ONVIF Profile G and S open standards
- H.265 and/or H.264 compression with triple-streaming functionality
- Edge recording up to 128GB SDHC card
- 1/1.8 CMOS image sensor
- Motorised IR Cut Filter
- Super Low Light: Color: 0.002 Lux @ (f1.2, AGC ON), 0 Lux IR on
- 3.8-16 mm lens
- Up to 50m IR illumination
- Up to 120dB Wide Dynamic Range
- Intelligence (Face detection, Audio Exception Detection, Intrusion Detection, De-focus Detection, Region of Interest (ROI), Electronic Image Stabilization (EIS), Defog, Scene Change Detection, Cross Line Detection, Advanced Motion Detection, Region Entrance Detection, Region Exit Detection, Object Removal, Object Left Behind, Object Counting)

# TVB-5801

TruVision 2MPX, Stainless Steel, super low light, IP VF lens bullet camera, 3.8-16mm, True D/N, WDR, 50M IR, Micro SD/SDHC/SDXC slot, 24 VAC, IP67

## Technical Specifications

### Camera

Sensor Size	1/1.8"
Max. Resolution	1080p
Sensor Scan	Progressive
Sensor Type	CMOS
Electronic Shutter	1/3s - 1/100,000s

### Lighting performance

Wide dynamic range (WDR)	True WDR
WDR	120 dB
Digital Noise Reduction	3D DNR
Day/Night	True Day/Night
Motorized IR Cut Filter	Yes
Color Sensitivity	0.002 lux @ (F1.2, AGC ON)
B/W Sensitivity	0 lux with IR on
InfraRed (IR)	Yes
IR Sensitivity	0 lux with IR
IR Range	Up to 50 m

### Encoding

Video Streams	3
Video Compression Main Stream	H.264, H.265
Video Compression Sub Stream	H.264, H.265, M-JPEG
Video Bit Rate	128kbps to 16Mbps
Main Stream Supported Resolutions	1280 x 720 (XVGA), 1280 x 960 (720p), 1920 x 1080 (1080p)
Sub Stream Supported Resolutions	1280 x 720 (XVGA), 1280 x 960 (720p), 176 x 144 (QCIF), 352 x 288 (CIF), 704 x 576 (4CIF)
Max. Resolution @ fps	1920 x 1080 @ 50 fps

### Lens

Lens Type	Varifocal
Focal length	3.8-16mm
F-stop	f1.2
Auto-iris	Yes

### Network

Supported Video Standards	CGI, ONVIF, PSIA
Supported Network Protocols	802.1x, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, Qos, RTP, RTSP, SMTP, SNMP, TCP/IP, UPnP

### Audio

Audio Compression	G.711, G.722.1, G.726, MP2L2
Audio In	1
Audio Out	1
Audio Bit Rate	32-128 Kbps (varies by compression standard)

### Alarm I/O

Alarm Inputs	1
Alarm Outputs	1

### Storage

Local Storage Support	Yes
Local Storage Type	Built-in Micro SD/SDHC/SDXC card slot
Max Storage Capacity	128GB

### Video intelligence

Basic Alarm Detection	Motion, Privacy Masking, Tamper
Video Analytics	Advanced motion detection, Audio exception, Cross line, De-focus, Defog, Electronic Image Stabilization (EIS), Face detection, Intrusion detection, Object counting, Object left behind, Object removal, Region entrance detection, Region exit detection, Scene change

### General

Technology	IP
Video Standard	NTSC, PAL
Display Modes	Hallway View, Mirror, ROI (Region Of Interest)
Software Compatibility	OnGuard, Prism, TruVision Navigator, TVRmobile, Web Browser

### Electrical

Power supply value	24 VAC
Power consumption	100 W

### Physical




Physical dimensions	465 x 190 x 180mm
Net weight	10.1 Kg
Colour	Grey
Material	Stainless Steel
Form Factor	Bullet

### Environmental

Operating temperature	-40 to +60°C
Relative humidity	<95% (non-condensing)
Environment	Outdoor
IP-rating	IP67

### Standards & regulation

Compliance	CE, FCC, REACH, RoHS, UL, WEEE
------------	--------------------------------



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.