

TVM-2202

TRUVISION 22" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market. Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability. These monitors are designed to perform 24/7 and are design with security applications in mind.



Capabilities

The TVM-2202 is a 22" class monitor, offering HDMI, VGA and BNC connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.

Details

- 22" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI
- BNC analog input

TVM-2202

TRUVISION 22" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Technical Specifications

S	SD	splay

21.5"
16:9
1,000:1
170° / 160°
5ms
250 cd/m ² (typ)
1920 x 1080 @ 60 HZ
NTSC/PAL Auto Detect
2W x 2
Built-in
Built-in
Built-in 1/1
1/1
1/1

Operations

PC Stereo In

Head Phone Out

Controls	Power, Up/Down, Left/Right, Source, OSD
	Menu
OSD	English, French, Spanish, German, Italian,
	Portuguese, Netherlands, Russian, Turkish
	Polish
Remote Control Support	Yes

Yes

No

General

Technology	LED
Filter Type	3D Combfilter, Deinterlace
Panel Lamp Life	30,000 hours
VESA compatibility	100 x 100 mm
Accessories Included	Manual, Power Adapter, Power Cord, Remote Control

Electrical

Power supply type	100 to 240 VAC
Power consumption	<30W

Physical

Housing Type	Plastic
Physical dimensions	542mm X 368mm X 207mm
Net weight	4.0 kg
Shipping weight	5.8 kg
Colour	Black

Environmental

Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	10 to 85%
Environment	Indoor

Standards & Regulations

Compliancy	CE



