



## CHOF230/HTR24

Fliptop Housing 230mm IP66 & Cable Management

#### Overview

Gain easy access to your outdoor security cameras with innovative fliptop-style housing. The CHOF230 model accommodates a camera and lens of 230 mm.

#### Ease of use.

Open the housing heavy-duty latch, flip up the hinged top, and easily install or adjust a camera.

### Sturdy construction

Die-cast aluminum gives the CHOF230 housing strength and durability while keeping each unit lightweight. Without the blower,the housing has weatherproof ratings of IP66.

### Managed cable guiding

A colum in the wall bracket allows you to route one or two cables through individual outlets into the bottom of the housing . Avoid damage to cables while keeping the inside of the housing dry.

## **Environmental protection**

The heavy-duty aluminum sunshield protects the camera from too much light. For environments where weather conditions demand heating or cooling, the CHOF230 has a option for heater and/or blower.

### Mounting options

Optional mounting brackets are available for CHOF230 housing. Position a camera on a wall or in a corner, or on a pole.



#### Standard Features

- Die-cast aluminum construction
- Weatherproof with an IP66 rating
- · Flips open for easy access to the security camera
- Optional heater/blower kit available
- · Interchangeable cable access
- · Multiple mounting options available
- · Cable managed wall bracket

# CHOF230/HTR24

## Fliptop Housing 230mm IP66 & Cable Management

## Specifications

Dimensions	230 x 76 x 76 mm
Power	31 W
Operating temperature	-20 to +50°C
Material	Die-cast aluminium
Colour	White RAL9002
Window	65 x 65 mm
IP rating	IP66

## **Ordering Information**

Part No.	Description
CHOF230/HTR24	Fliptop Housing 230mm IP66 & Cable Management

