



# CHOF270/IP66/24VAC

Fliptop Housing 270mm 24VAC PSU - 230VAC Heater IP66 & Cable

## Overview

---

Gain easy access to your outdoor security cameras with innovative fliptop-style housing. The CHOF270 model accommodates a camera and lens of 270 mm.

## Ease of use.

---

Open the housing heavy-duty latch, flip up the hinged top, and easily install or adjust a camera.

## Sturdy construction

---

Die-cast aluminum gives the CHOF270 housing strength and durability while keeping each unit lightweight. Without the blower, the housing has weatherproof ratings of IP66.

## Managed cable guiding

---

A column in the wall bracket allows you to route one or two cables through individual outlets into the bottom of the housing. Avoid damage to cables while keeping the inside of the housing dry.

## Environmental protection

---

The heavy-duty aluminum sunshield protects the camera from too much light. For environments where weather conditions demand heating or cooling, the CHOF270 has an option for heater and/or blower.

## Mounting options

---

Optional mounting brackets are available for CHOF270 housing. Position a camera on a wall or in a corner, or on a pole.



## Standard Features

---

- Die-cast aluminum construction
- Weatherproof with an IP66 rating
- Flips open for easy access to the security camera
- Optional heater/blower kit available
- Interchangeable cable access
- Multiple mounting options available
- Cable managed wall bracket

# CHOF270/IP66/24VAC

Fliptop Housing 270mm 24VAC PSU - 230VAC Heater IP66 & Cable

## Specifications

Dimensions	270 x 76 x 76 mm
Power	31 W
Operating temperature	-20 to +50°C
Material	Die-cast aluminium
Colour	White RAL9002
Window	65 x 65 mm
IP rating	IP66

## Ordering Information

Part No.	Description
CHOF270/IP66/24VAC	Fliptop Housing 270mm 24VAC PSU - 230VAC Heater IP66 & Cable Management

