



CHOW300/IP66/24VAC

Camera Housing IP66 24VAC PSU - 230v Heater & Cable Management

This range of camera housings has been carefully designed not only to meet the harsh environmental requirments of todays CCTV systems, but also to offer a wide range of fixings and specifications.

These stylish housings have been thoughtfully designed so that they not only look good, but are also easy to install and service. they all feature the slide and hang servicing facility. The top of the housing, when unsecured, slides forward and then hangs below the housing body giving maximum accessability to the camera and lens inside.

The 300 series are constructed from either Die-cast or extruded aluminium protected with an Epoxy paint coating to give durability. Within the 300 series of housings there is a cable management bracket option. This feature hides and protects the system cables where neccessary, due to either aesthetic or anti vandalism requirements.



Standard Features

- · Aluminium or ABS construction
- IP 66 or IP 65 versions
- · Cable management version
- · Wall or ceiling mount
- Polyester paint finish
- Internal versions
- External versions with heaters and thermostats
- Optional internal 24 V ac camera power supply

CHOW300/IP66/24VAC

Camera Housing IP66 24VAC PSU - 230v Heater & Cable Management

Specifications

Material	Die-cast or extruded aluminium, epoxy paint coated
IP rating	IP66 or IP65
Bracket options	Ceiling,wall or wall mount cable management version
Heater	220 VAC
PSU	220 VAC input / 24 VAC output
Heater	70 W
Useable internal length	300 mm
Dimensions (W x H x D)	124 x 121 x 410 mm

Ordering Information

Part No.	Description
CHOW300/IP66/24VAC	Camera Housing IP66 24VAC PSU - 230v Heater & Cable Management



