



CHW270/24HTR/IP66

Camera Housing & Wall Bracket 24 VAC Heater & Sunshield

This range of low cost entry level camera housings has been carefully designed not only to meet the harsh environmental requirements of today's CCTV systems, but also to offer a wide range of fixings and specifications. Camera Housing & Wall Bracket 24VAC Heater & Sunshield offers a low voltage option

The 270 series of housings, consists of ABS body and aluminium sunshield. The standard CHW 270 has conventional 10mm cable glands and accepts standard flexible conduit. The CHW 270F is a high specification housing that includes a cable accessory kit. The kit includes a 0.75m length of plastic flexible conduit of 30mm diameter. It is secured at each end with two nylon adapters. This design permits a professional and aesthetically pleasing finish to installation

All the Aritech range of camera housings, with exception of CWH/270 internal housing are rated to IP66/IP65.



Standard Features

- Aluminium or ABS construction
- IP66
- Cable management version
- Wall or ceiling mount
- Polyester paint finish
- Internal versions
- External versions with heaters and thermostats
- Optional internal 24 VAC camera power supply

CHW270/24HTR/IP66

Camera Housing & Wall Bracket 24 VAC Heater & Sunshield

Specifications

Material	Die-cast or extruded aluminium
	Epoxy paint coated
	ABS or glass re-inforced nylon
IP rating	IP66
Mounting options	Wall brackets
Voltage	
Heater	24 VAC
PSU	220 VAC input / 24 VAC output
Blower	N/A
Power	13 W
Heater	7 W (24 VAC)
Blower	N/A
Useable internal length	270 mm
Dimensions (W x H x D)	128 x 138 x 410 mm

Ordering Information

Part No.	Description
CHW270/24HTR/IP66	Camera Housing & Wall Bracket 24 VAC Heater & Sunshield

