



GE
Security

Product Data Sheet

GE-CD816A

8 Input to 16 Output Video Distribution Amplifier



Standard Features

- 8 Input 16 Output Video Distribution Amplifier
- Wide bandwidth, video gain compensation amplification
- HF compensation
- Sharpness and Brightness adjustment
- Transmission range: 1000 meters (RG59 coaxial cable)

GE-CD816A

8 Input to 16 Output Video Distribution Amplifier

Specifications

Video Input Channels

- 8

Video Output Channels

- 16

Video Input Level

- 0.8 - 1.2V pk-pk (Standard) 75 Ohms

Video Output Level

- 1V pk-pk 75 Ohms

Video Bandwidth

- 10hz - 10Mhz

Power Supply

- 12VDC (included)

Power Consumption

- 500 mA

Dimensions (WxHxD)

- 482 x 170 x 44 mm

Weight

- 2600g

Material

- Metal Black

Diagram

Ordering Information

GE-CD816A

8 Input to 16 Output Video Distribution Amplifier



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit [GE Security online](http://www.gesecurity.net) or contact your GE Security sales representative.

IPS-GE-CD816A-2007-03-27 15:01:16 Released : 27.03.2007;