



TVB-2101

TruVision IR Bullet High-Res Camera, PAL, 700 TVL, Fixed 3.6 mm Lens

Overview

The TruVision™ line includes a comprehensive family of 960H infrared (IR) cameras for stand-alone or basic integrated installations that are flexible and scalable to accommodate future growth. Ideal for surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision IR line has the right cameras for your job and can help you stay within budget constraints without compromising security needs.

These flexible cameras can see in total darkness, providing color images by day and black-and-white images under IR operation in low-light applications. Form factors include omnidirectional dome and traditional bullet cameras. Dome models allow for ceiling or wall mounting while still maintaining a level field of view. The bullet models offer a familiar form factor that can be ceiling or wall mounted. TruVision IR dome and bullet cameras are also available in fixed lens and varifocal lens models.

Application

Built for long-lasting service and plug-and-play functionality, the TruVision IR line provides a value-based solution that is ideal for applications ranging from residential to office buildings.

Designed for low-light and complete-darkness environments, TruVision cameras' balanced IR capabilities and multiple resolution options offer the perfect camera for each situation. With weather-resistant options that are well suited for indoor and outdoor applications, TruVision cameras represent sensible, secure video surveillance you can depend on.



Standard Features

- IR illumination for optimal viewing in low- to o-light environments
- Provide flexible installation options and ensure the right camera for the job
- Compatible with all analog CCTV recording devices and equipment
- IP67 ratings for weather-resistant performance
- 960H (700) TV Lines
- 3.6 mm fixed lens
- IR range of 15 m
- 12 VDC
- Bracket included

TVB-2101

TruVision IR Bullet High-Res Camera, PAL, 700 TVL, Fixed 3.6 mm Lens

Specifications

Camera

Pick-up device:	1/3" Exview CCD II
Total pixels (H x V):	PAL: 1020 x 596 / NTSC:1020 x 508
Effective pixels (H x V):	PAL: 976 x 582 / NTSC:976 x 494
Resolution:	700 TV Lines
Sync. system:	Internal
Scanning system:	2:1 Interlace
S/N ratio:	More than 50 dB (AGC OFF)
Electronic shutter:	Auto 1/60 (1/50) to 1/100,000 s
Min. illumination:	0.2 lux color / F2.0; 0.00 lux IR ON
Video output:	Composite 1.0 Vp-p / 75 ohm
IR distance:	15 m (18 pcs IR LED)
IR trigger:	3.1 lux / 3.7 lux (IR on/off)
Lens type:	Fixed: 3.6 mm
Wide Dynamic Range:	DWDR
Digital noise reduction:	2DNR

Electrical

Power source:	12 VDC
Power consumption:	77 mA (IR off), 263 mA (IR on)
Current:	0.924W Max (IR off), 3.156 W Max (IR on)

Environmental & Physical

Weight:	310 g (0.68 lb.)
Dimensions:	57 x 81.6 mm (2.24 x 3.21 in.)
Operation temperature:	-30 ° to +60 °C (-22 ° to +140 °F)
Storage temperature:	-20 to +70° C (-4 to +158° F)
Weather resistant:	IP67

Ordering Information

Part No.	Description
TVB-2101	TruVision IR Bullet High-Res Camera, PAL, 700 TVL, Fixed 3.6 mm Lens

