



## TVC-5401

TruVision IP Box Camera, 2 MPX, WDR

### Overview

The TruVision line of IP box form factor cameras leverages the latest H.265 video compression technology to bring state-of-the-art, high-definition pictures to the mass video surveillance market. With camera resolutions of 2, 3, or 5 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advanced technology and signal processing capability, they effectively capture video under challenging conditions.

H.265 and/or H.264 compression with triple-streaming capability provide even greater flexibility for managing bandwidth and storage use. Select models feature Super Low Light technology, which provides a clear image in low lighting conditions with a minimum of “grainy” interference. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.

These cameras go above and beyond standard motion detection with enhanced alarm capabilities, including cross line, intrusion, defocus and face detection features. Each is user-configurable to best suit the installation environment. A Region of Interest function ensures specific portions of an image are given priority during instances of high network traffic or network degradation.

Location-specific functions include a Hallway View Mode to provide a portrait view of a hallway or corridor, a De-Fog Mode to help resolve images through fog or rain and Electronic Image Stabilization for installations subject to physical vibration or shaking.



### Standard Features

- Maximum Resolution: 1980 x 1080
- Maximum Real Time Resolution: 1980 x 1080 @ 50 fps
- Designed to PSIA and ONVIF Profile G and S open standards
- H.265 and/or H.264 compression with triple-streaming functionality
- Edge recording up to 128GB SDHC card
- 1/1.8” CMOS image sensor
- Motorized IR Cut Filter
- Super Low Light: Color: 0.002 Lux @ (F1.2, AGC ON), 0 Lux IR on
- Up to 120dB Wide Dynamic Range
- Intelligence (Face detection, Audio Exception Detection, Intrusion Detection, De-focus Detection, Region of Interest (ROI), Electronic Image Stabilization (EIS), Defog, Scene Change Detection, Cross Line Detection, Advanced Motion Detection, Region Entrance Detection, Region Exit Detection, Object Removal, Object Left Behind, Object Counting)

# TVC-5401

TruVision IP Box Camera, 2 MPX, WDR

## Specifications

<b>Camera</b>	
Sensor:	2 MPX 1/18" Progressive Scan CMOS
Day/Night:	Motorized IR Cut Filter
IP Compression/Standard:	H.265/ H.264 / MJPEG
Maximum Resolution (@ FPS):	1980 x 1080 (50 fps)
Maximum Real Time Resolution (@ FPS):	50Hz: 50 fps (1920 x 1080, 1280 x 960, 1280 x 720) 60Hz: 60 fps (1920 x 1080, 1280 x 960, 1280 x 720)
Multiple Streaming:	Triple Streams
Video Bit Rate:	128 Kbps to 16 Mbps, adjustable
S/N Ratio:	52 dB (AGC OFF)
Auto Exposure (shutter):	50 Hz: 1/3s to 1/100,000s 60 Hz: 1/3s to 1/100,000s
Composite Output (BNC):	PAL, 1.0 Vp-p @ 75 ohm
<b>Lighting performance</b>	
Wide Dynamic Range	WDR
WDR in dB	120dB
Digital noise reduction	3D DNR
Highlight compensation (HLC)	No
Day/Night	True D/N
Motorized IR Cut Filter	Yes
Color sensitivity	Color: 0.002 Lux @ (F1.2, AGC ON), B/W: 0.0002 Lux @ (F1.2, AGC ON)
IR Range	N/A
IR Wavelength	N/A
<b>Lens</b>	
Control type:	N/A
Focal length:	N/A
Zoom lens:	N/A
Autofocus:	Yes
<b>Electrical</b>	
Voltage Input:	12VDC / 24 VAC, PoE (802.3af)
Power Consumption:	10 W
Current:	850 mA
Auxiliary Power	N/A
<b>Network</b>	
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, ezDDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv6. ONVIF, PSIA, CGI
PoE IEEE:	802.3af
Standard & Integration	ONVIF Profile (G,S), PSIA, CGI
<b>LocalStorage</b>	
Media:	MicroSD/micro SDHC/ microSDXC
Capacity:	Up to 128GB
Input:	Audio in / Mic in (line level)
Output:	Audio out
Audio bit rate (protocol)	G.711ulaw, G.711alaw, MP2L2, G.726, PCM
<b>Camera Alarm</b>	
Basic:	Motion Detection, Tamper Proof, Privacy Mask
Advanced:	Face detection, Audio Exception Detection, Intrusion Detection, De-focus Detection, Region of Interest (ROI), Electronic Image Stabilization (EIS), Defog, Scene Change Detection
	Cross Line Detection, Advanced Motion Detection, Region Entrance Detection, Region Exit Detection, Object Removal, Object Left Behind, Object Counting
Input/Output:	1 input / 1 output
<b>Display</b>	
Display mode:	N/A
OSD:	N/A
<b>Mechanical/ Environmental</b>	
Camera type:	Box
Dimensions:	69.8 x 58 x 145mm (2.75 x 2.28 x 5.71 in.)

Weight:	830 g (1.83 lbs.)
Storage Temperature:	-30° to 60°C (-22° to 140°F)
Operating Temperature:	-30° to 60°C (-22° to 140°F)
Environmental Rating:	N/A
Vandal Rating:	N/A
Outdoor:	With outdoor housings
<b>Regulation</b>	
Compliance:	FCC, CE, UL, WEEE, RoHS, REACH

## Ordering Information

Part No.	Description
TVC-5401	TruVision IP Box Camera, 2 MPX, WDR

