



TVC-M1220-1U-P

1.3 MPX HD Box Camera ONVIF/PSIA, PAL

Overview

TruVision™ IP and IP megapixel box cameras bring state-of-the-art, high definition pictures to the mass video surveillance market. With a wide variety of camera resolutions ranging from standard resolution through 5 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advance technology and signal processing capabilities, the effectively capture video under challenging conditions.

Compression & streaming

These TruVision cameras utilize H.264 compression technology with dual-stream capability, making it easy to manage the camera's bandwidth usage.

Fully designed to adhere to PSIA and ONVIF open communication standards as well as supporting a CGI command set, these cameras allow for simple integration into any IP system. Video streams can be set for high or low bandwidth and images can be streamed for live viewing or sent to a designated recording location.

Additional Features

Featuring an integrated browser and available SDHC memory card storage capabilities, TruVision IP and IP Megapixel cameras simplify remote, live monitoring/playback of edge-recorded video and audio. Recording on the memory card also provides a level of redundancy in case of unforeseen network disruptions.

Form Factor

The box version of this camera range provides flexible solutions for installation. Available with a wide range of appropriate lenses as well as brackets and wall mounts, these cameras can provide a solution to the most advanced of needs.

Typical application areas are places where crisp images are required such as retail, banking, airports, gaming or mass transit. Using the IP66 rated housings, these cameras also provide a vandal-proof, weather-proof solution.



Standard Features

- Maximum Resolution: 1280x960 @ 25 fps
- Maximum Real Time Resolution: 1280x960 @ 25 fps
- Designed to PSIA and ONVIF open standards
- H.264 compression with dual streaming functionality
- Edge recording up to 32GB SDHC card
- 1/3" CMOS image sensor
- Motorized IR Cut Filter
- 0.04 Lux (Color)
- Motion detection
- Privacy masking
- 1 alarm Input/Output

TVC-M1220-1U-P

1.3 MPX HD Box Camera ONVIF/PSIA, PAL

Specifications

Camera	
Sensor:	1.3 MPx 1/3" Progressive Scan CMOS
Day/Night:	Motorized IR Cut Filter
IP Compression/Standard:	H.264 PSIA/ONVIF
Maximum Resolution (@ FPS):	1280 X 960 (25 FPS)
Maximum Real Time Resolution (@ FPS):	1280 X 960 (25 FPS)
Dual Streaming:	Yes
Video Bit Rate:	32 Kbps to 8 Mbps, adjustable
Sensitivity:	0.04 Lux (Color)
S/N Ratio:	50 dB
Auto Exposure (shutter):	1/25s to 1/100,000s
Composite Output (BNC):	PAL, 1.0 Vp-p @ 75 ohm
Lens :	C/CS (autoiris)
Electrical	
Voltage Input:	12 VDC PoE (IEEE 802.3af)
Power Consumption:	5.5 Watts (8.5 Watts w/ IR cut filter motor)
I/O Connection:	Terminal Plug
Network	
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, FTP, 802.1x, QoS, HTTPS
PoE IEEE:	802.3af
LocalStorage	
Media:	SDHC (Secure locked card slot)
Capacity:	Up to 32GB
Audio G.711/G.726	
Input:	1 ch. 3.5 mm audio interface(2.0 - 2.4 Vp-p, 1 kOhm)
Output:	1 ch. 3.5 mm audio interface(Line level, 600 Ohm)
Audio Bitrate:	16Kbps
CameraAnalytics	
Motion Detection:	Yes
Privacy Masking:	Yes
Alarm	
Alarm Input:	1
Alarm Output:	1 Form C alarm relay
I/O Connection:	Screw Terminal
Mechanical/ Environmental	
Dimensions:	68 x 57 x 133mm (2.68 x 2.24 x 5.27 in.)
Weight:	0.5kg (1.1bs)
Storage Temperature:	-20 to 70°C (-4 to 158°F)
Operating Temperature:	-10°C to 60°C (14 to 140°F)
Environmental Rating:	Indoor
PC Requirements	
Intel-based PC:	1 Ghz or faster
Memory:	1 GB RAM
Operating System:	Windows® XP, Vista or 7
CGI:	Direct X 9.0 or later
Browser:	Microsoft Internet Explorer 6.0 or later

Ordering Information

Part No.	Description
TVC-M1220-1U-P	1.3 MPX HD Box Camera ONVIF/PSIA, PAL

