



## Product Data Sheet

# TVC-N240-1-P

4CIF WDR Box Camera ONVIF/PSIA

### Overview

TruVision™ IP and IP megapixel box cameras bring state-of-the-art, high definition pictures to the mass video surveillance market. With a wide variety of camera resolutions ranging from standard resolution through 5 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advance technology and signal processing capabilities, the effectively capture video under challenging conditions.



### Compression & streaming

These TruVision cameras utilize H.264 compression technology with dual-stream capability, making it easy to manage the camera's bandwidth usage.

Fully designed to adhere to PSIA and ONVIF open communication standards as well as supporting a CGI command set, these cameras allow for simple integration into any IP system. Video streams can be set for high or low bandwidth and images can be streamed for live viewing or sent to a designated recording location.



### Additional Features

Featuring an integrated browser and available SDHC memory card storage capabilities, TruVision IP and IP Megapixel cameras simplify remote, live monitoring/playback of edge-recorded video and audio. Recording on the memory card also provides a level of redundancy in case of unforeseen network disruptions.

### Standard Features

- Maximum Resolution: 704x576 @ 25 fps
- Maximum Real Time Resolution: 704x576 @ 25 fps
- Designed to PSIA and ONVIF open standards
- H.264 compression with dual streaming functionality
- Edge recording up to 32GB SDHC card
- 1/3" CMOS image sensor
- Wide Dynamic Range
- Motorized IR Cut Filter
- 0.35 Lux (Color)
- Motion detection (396 zones)
- Privacy masking (396 zones)
- 1 alarm Input/Output

### Form Factor

The box version of this camera range provides flexible solutions for installation. Available with a wide range of appropriate lenses as well as brackets and wall mounts, these cameras can provide a solution to the most advanced of needs. Typical application areas are places where crisp images are required such as retail, banking, airports, gaming or mass transit. Using the IP66 rated housings, these cameras also provide a vandal-proof, weather-proof solution.

# TVC-N240-1-P

## 4CIF WDR Box Camera ONVIF/PSIA

### Specifications

#### Camera

- Sensor: 1/3" WDR CCD
- Day/Night: Motorized IR Cut Filter
- IP Compression/Standard: H.264 PSIA/ONVIF
- Maximum Resolution (@ FPS): 704 X 576 (25 FPS)
- Maximum Real Time Resolution (@ FPS): 704 X 576 (25 FPS)
- Dual Streaming: Yes
- Video Bit Rate: 32 Kbps to 8 Mbps, adjustable
- Sensitivity: 0.35 Lux (Color)
- S/N Ratio: > 50 dB
- Auto Exposure (shutter): 1/25s to 1/100,000s
- Composite Output (BNC): PAL, 1.0 Vp-p @ 75 ohm (NTSC Selectable)
- Lens : C/CS (autoiris)

#### Electrical

- Voltage Input: 12 VDC PoE (IEEE 802.3af)
- Power Consumption: 5.5 Watts (10.5 Watts w/ IR cut filter motor)
- I/O Connection: Terminal Plug RJ45

#### Network

- Network Protocols: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTCP, PPPoE, SMTP, NTP
- Ethernet/IP: CoS 802.1 p/Q, QoS, IPv4
- PoE IEEE: 802.3af

#### Local Storage

- Media: SDHC (Secure locked card slot)
- Capacity: Up to 32GB

#### Audio G.711

- Input: 1 ch. 3.5 mm audio interface (2.0 - 2.4 Vp-p, 1 kOhm)
- Output: 1 ch. 3.5 mm audio interface (Line level, 600 Ohm)
- Audio Bitrate: 16Kbps

#### Camera Analytics

- Motion Detection: On-board 396 zones per camera
- Privacy Masking: On-board 396 zones per camera


#### Alarm

- Alarm Input: 1
- Alarm Output: 1 Form C alarm relay
- I/O Connection: Screw Terminal

#### Mechanical/ Environmental

- Dimensions: 68 x 57 x 133mm (2.68 x 2.24 x 5.27 in.)
- Weight: 0.5kg (1.1bs)
- Storage Temperature: -20 to 70°C (-4 to 158°F)

### Diagram



- Operating Temperature: -10°C to 60°C (14 to 140°F)
- Environmental Rating: Indoor

#### PC Requirements

- Intel-based PC: 1 Ghz or faster
- Memory: 1 GB RAM
- Operating System: Windows® XP, Vista or 7
- CGI: Direct X 9.0 or later
- Browser: Microsoft Internet Explorer 6.0 or later

### Ordering Information

TVC-N240-1-P

4CIF WDR Box Camera ONVIF/PSIA

