



TVD-DOME5-HR9-P

TruVision™ Dome, PAL, 550TVL, Color

The TruVision dome camera provides outstanding video surveillance performance while offering a cost effective security solution. Equipped with a varifocal lens and engineered for superior resolution, this camera delivers crisp, detailed images while being flexible enough to meet the needs of most applications.

Small and lightweight, the TruVision plastic dome camera represents a strong value for users looking for reliable security in smaller venues. With 550TVL color and a 9mm–22mm autoiris lens, this TruVision dome is well suited to secure a variety of applications including quick-service restaurants, retail and smallbusiness environments.



Standard Features

- Superior image performance
- 550 TVL color
- Flexible form factor
- Varifocal auto-iris lens
- 0.2 lux @ F2.0
- 9mm to 22mm AI lens
- 12VDC or 24VAC power input

TVD-DOME5-HR9-P

TruVision™ Dome, PAL, 550TVL, Color

Specifications

Signal system	PAL/CCIR
Image sensor	1/3 in. interline transfer Sony CCD
Picture elements	PAL:795(H) x 596(V)
Scanning system	625 lines, 50 fields (PAL/CCIR)-2:1 interface
Signal-to-noise ratio	> 48 dB
Resolution	550 TVL
Sensitivity	0.2 lux @ f2.0
White balance	Automatic
AGC	ON
Synchronization	Internal Sync
Video output	1.0 V p-p 75 ohm unbalanced
Electronic shutter	AES 1/50 (1/60 sec) to 1/100,000 sec
Power supply	12 VDC (500 mA) or 24 VAC (500 mA)
Power consumption	< 3 W (max); 230mA / 210mA (max), 12 VDC/24 VAC
Environmental	Weight: 225 g/370 g (N.W./G.W.) Dimensions: 4.18 x 3.26 in. (106.4 x 83 mm) Operating temperature: -10°C to 50°C

Ordering Information

Part No.	Description
TVD-DOME5-HR9-P	TruVision™ Dome, PAL, 550TVL, Color

