



# TVD-M1225V-2U-P

1.3 MPX HD Indoor IR Dome ONVIF/PSIA

#### Overview

TruVision™ IP and IP megapixel IR compact dome cameras bring state-of-the-art, high definition pictures to the mass video surveillance market. With a wide variety of camera resolutions ranging from standard resolution through 5 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advance technology and signal processing capabilities, the effectively capture video under challenging conditions.

#### Compression & streaming

These TruVision cameras utilize H.264 compression technology with dual-stream capability, making it easy to manage the camera's bandwidth usage.

Fully designed to adhere to PSIA and ONVIF open communication standards as well as supporting a CGI command set, these cameras allow for simple integration into any IP system. Video streams can be set for high or low bandwidth and images can be streamed for live viewing or sent to a designated recording location.

#### **Additional Features**

Featuring an integrated browser and available SDHC memory card storage capabilities, TruVision IP and IP Megapixel cameras simplify remote, live monitoring/playback of edge-recorded video and audio. Recording on the memory card also provides a level of redundancy in case of unforeseen network disruptions.

#### Form Factor

The IR compact dome version of the TruVision IP & Megapixel range provides a vandal proof IR indoor solution up to five megapixel. Available with a wide range of appropriate brackets and wall mounts, these cameras can provide a solution to the most advanced of needs.

Typical application areas are places where crisp images are required, even in pitch black darkness, such as retail, banking, airports, gaming or mass transit.



#### Standard Features

- Maximum Resolution: 1280x960 @ 25 fps
- Maximum Real Time Resolution: 1280x960 @ 25 fps
- Designed to PSIA and ONVIF open standards
- · H.264 compression with dual streaming functionality
- Edge recording up to 32GB SDHC card
- 1/3" CMOS image sensor
- · Motorized IR Cut Filter
- 0.03 Lux (Color)
- 0 Lux (IR on)
- Up to 10m IR Illumination
- Motion detection
- Privacy masking
- 2 Input/Output

# TVD-M1225V-2U-P

# 1.3 MPX HD Indoor IR Dome ONVIF/PSIA

### **Specifications**

| Camera                                |   |
|---------------------------------------|---|
| Sensor:                               | 1.3 MPx 1/3" Progressive Scan CMOS  |
| Day/Night:                            | Motorized IR Cut Filter   |
| IR LEDs (Range):                      | Yes (10m)   |
| IP Compression/Standard:              | H.264 PSIA/ONVIF  |
| Maximum Resolution (@ FPS):           | 1280 X 960 (25 FPS)   |
| Maximum Real Time Resolution (@ FPS): | 1280 X 960 (25 FPS)   |
| Dual Streaming:                       | Yes   |
| Video Bit Rate:                       | 32 Kbps to 8 Mbps, adjustable   |
| Sensitivity:                          | 0.03 Lux (Color) 0 Lux (IR On)  |
| S/N Ratio:                            | 50 dB   |
| Auto Exposure (shutter):              | 1/25s to 1/100,000s   |
| Composite Output (BNC):               | PAL, 1.0 Vp-p @ 75 ohm  |
| Lens:                                 | 2.7 to 9 mm, F1.2 Autoiris  |
| Electrical                            |   |
| Voltage Input:                        | 12 VDC PoE (IEEE 802.3af)   |
| Power Consumption:                    | 7.5 Watts (9.5 Watts IR on)   |
| I/O Connection:                       | Terminal Plug   |
| Network                               |   |
| Network Protocols:                    | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP,<br>RTSP, PPP0E, SMTP, NTP, UPnP, SNMP, FTP,<br>802.1x, QoS, HTTPS |
| PoE IEEE:                             | 802.3af   |
| LocalStorage                          |   |
| Media:                                | SDHC (Secure locked card slot)  |
| Capacity:                             | Up to 32GB  |
| Audio G.711                           |   |
| Input:                                | 1 ch. 3.5 mm audio interface (2.0 - 2.4 Vp-p, 1 kOhm)   |
| Output:                               | 1 ch. 3.5 mm audio interface (Line level, 600 Ohm)  |
| Audio Bitrate:                        | 16Kbps  |
| Camera Analytics                      |   |
| Motion Detection:                     | Yes   |
| Privacy Masking:                      | Yes   |
| Alarm                                 |   |
| Alarm Input:                          | 2   |
| Alarm Output:                         | 2 Form C alarm relay  |
| I/O Connection:                       | Terminal Plug   |
| Mechanical/ Environmental             |   |
| Dimensions:                           | 140 × 120 mm (5.5 x 4.7 in.)  |
| Weight:                               | 1.4 kg (3.09 lbs)   |
| Storage Temperature:                  | -20 to 70°C (-4 to 158°F)   |
| Operating Temperature:                | -10°C to 60°C (14 to 140°F)   |
| Environmental Rating:                 | Indoor Vandal-Resistant IK10  |
| PC Requirements                       |   |
| Intel-based PC:                       | 1 Ghz or faster   |
| Memory:                               | 1 GB RAM  |
| Operating System:                     | Windows® XP, Vista or 7   |
| CGI:                                  | Direct X 9.0 or later   |
| Browser:                              | Microsoft Internet Explorer 6.0 or later  |
|                                       |   |

## **Ordering Information**

| Part No.        | Description                          |
|-----------------|--------------------------------------|
| TVD-M1225V-2U-P | 1.3 MPX HD Indoor IR Dome ONVIF/PSIA |



