Product Data Sheet



TVT-2101

TruVision IR Turret High-Res Camera, PAL, 700 TVL, 3.6 mm Lens

Overview

The TruVision[™] line includes a comprehensive family of 960H infrared (IR) cameras for standalone or basic integrated installations that are flexible and scalable to accommodate future growth. Ideal for surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision IR line has the right cameras for your job and can help you stay within budget constraints without compromising security needs.

These flexible cameras can see in total darkness, providing color images by day and black-and-white images under IR operation in low-light applications. Form factors include omnidirectional dome and traditional bullet cameras. Dome models allow for ceiling or wall mounting while still maintaining a level field of view. Single gang adaptor plates are included with the turret models, while the bullet models offer a familiar form factor that can also be ceiling or wall mounted. TruVision IR dome and bullet cameras are also available in fixed lens and varifocal lens models.

Application

Built for long-lasting service and plug-and-play functionality, the TruVision IR line provides a valuebased solution that is ideal for applications ranging from residential to office buildings.

Designed for low-light and complete-darkness environments, TruVision cameras' balanced IR capabilities and multiple resolution options offer the perfect camera for each situation. With weather-resistant options that are well suited for indoor and outdoor applications, TruVision cameras represent sensible, secure video surveillance you can depend on.



Standard Features

- IR illumination for optimal viewing in low- to o-light environments
- Provide flexible installation options and ensure the right camera for the job
- Compatible with all analog CCTV recording devices
 and equipment
- IP67 ratings for weather-resistant performance
- 960H (700) TV Lines
- 3.6 mm lens
- IR range of 15 m
- 12 VDC

TVT-2101

TruVision IR Turret High-Res Camera, PAL, 700 TVL, 3.6 mm Lens

Specifications

Camera	
Pick-up device:	1/3" EXview HAD CCD II
Total pixels:	PAL: 1020 × 596 / NTSC:1020 × 508
Effective pixels:	PAL: 976 × 582 / NTSC:976 × 494
Resolution:	700 TV Lines
Sync. system:	Internal
Scanning system:	2:1 Interlace
S/N ratio:	More than 50 dB (AGC OFF)
Electronic shutter:	Auto 1/60 (1/50) to 1/100,000 sec.
Min. illumination:	0.2 lux color / F2.0; 0.00 lux IR ON
Video output:	Composite 1.0 Vp-p / 75 ohm
IR distance:	15 m / 49 ft. (14 pcs IR LED)
IR trigger:	3.1 lux / 3.7 lux IR ON/OFF
Lens type:	Fixed lens: 3.6 mm
Wide Dynamic Range:	DWDR
Digital noise reduction:	2DNR
Electrical	
Power source:	12 VDC
Power consumption:	2.41 W (IR ON)
Current:	201mA (IR ON)
Environmental & Physical	
Weight:	390 g (0.86lb)
Dimensions:	69 × 94 mm (2.72in × 3.7 in.)
Operation temperature:	-30 to 60° C (-22 to 140° F)
Storage temperature:	-20 to 70° C (-4 to 158° F)
Weather resistant:	IP67

Ordering I	nformation
------------	------------

Part No.	Description
TVT-2101	TruVision IR Turret High-Res Camera, PAL, 700 TVL, 3.6 mm Lens



