


POE series power supply unit

PoE power supply 48V DC for up to 16 IP cameras



EN*

CODE: **POE1648** v.1.0/1
TYPE: **PoE 48V/6A** PoE power supply for up to 16 IP cameras.



PSU features:

- the 16x0,35A/48V DC power output for powering 16 cameras IP
- output voltage adjustment 41V± 56V DC
- Wide range of supply voltage: 90±264V AC
- high efficiency: 89%
- designed for 10Mbit/s and 100Mbit/s network
- LED optical indication
- protections:
 - SCP short-circuit protection
 - OVP overvoltage protection
 - Surge protection
 - Antisabotage protection
 - OLP overload protection
- warranty – 2 year from the production date

DESCRIPTION

The PSU is designed for supply of up to 16 webcams requiring stabilized voltage of **48V DC**. The output voltage can be adjusted with a potentiometer between **41V±56V DC**. The power is carried over the spare pairs (4/5 & 7/8), which, according to the Ethernet network standard, are not used for data transmission (data transmission uses 1/2 and 3/6 data pairs). The PSU is housed in a metal enclosure with signaling panel equipped with a microswitch indicating door opening (front cover).

The PSU can not be used in Gigabit Ethernet networks, where all twisted pairs are involved in the transmission of data!

POE series power supply unit

PoE power supply 48V DC for up to 16 IP cameras



SPECIFICATIONS	
PSU type:	A (EPS - External Power Source)
Mains supply:	90÷264V AC
Current consumption:	2A@230VAC max.
PSU's power:	269W max.
Efficiency:	89%
Output voltage:	48V DC
The adjustment range of the output voltage:	41÷56V DC
Output current:	16 x 0,35A (ΣI=5,6A) max.@48V
Ripple voltage	240mV p-p max.
Short-circuit protection SCP	105% ÷ 135% of PSU power, automatic recovery
Overload protection OLP	105% ÷ 135% of PSU power, automatic recovery
Surge protection	varistors
Overvoltage protection OVP:	58÷68V DC
Antisabotage protection: - TAMPER output indicating enclosure opening	- microswitch, NC contacts (enclosure closed), 0,5A@50V DC (max.)
Optical indication of operation:	Yes –LED lights
Operating conditions:	2nd environmental class, -10 °C÷40 °C
Enclosure:	DC01 steel plate, 1,0mm, color RAL 9003
Dimensions:	291 x 387 x 101+15 (WxHxD) [mm] (+/-2)
Net/gross weight:	4,5kg / 4,8kg
Closing:	Cylindrical screw x 2 (at the front) (lock assembly possible)
Declarations, warranty	CE, 2 year from the production date
Notes:	The enclosure has a 15mm distance from the mounting surface so the cables can be led. PSU cooling: fan cooling. Switch mode power supply: Φ0,63-2,05(AWG 26-10) PoE module: Φ0,5-2,05 (AWG 24-12) LAN1 ÷ LAN4 inputs: RJ45 8P8C, shielded PoE1 ÷ PoE4 outputs: RJ45 8P8C, shielded TAMPER output: wires 35cm