

RACK POWER CCTV series power supply unit

RACK mounted buffer power supply for up to 16 cameras and recorder



EN*

CODE: **RUPS1612RT** v.1.0/II
TYPE: **RUPS 13,8V/12V/20A/TOPIC** mounted buffer power supply
for up to 16 cameras and recorder.



Features:

- DC 13,8V/16x0,75A uninterruptible power supply for powering HD cameras ($\Sigma I = 12A$ max.)
- DC 12V/4A uninterruptible power supply of the recorder
- 16 outputs to cameras independently protected with 1A glass fuses
- the output for the recorder is protected with the 4A glass fuse
- wide range of mains supply AC: 176÷264V AC
- high efficiency 82%
- battery charging and maintenance control
- excessive discharging (UVP) protection
- battery output protection against short circuit and reverse connection
- battery charge current: 2A (batteries 1x17Ah / 1x28Ah / 1x40A / 1x65Ah)
- control of voltage presence at the AUX1 ÷ AUX16 outputs DVR
- acoustic indication of failure
- LED optical indication: AC, DC, TEMP, LoB, ALARM, AUX1 ÷ AUX16, DVR
- the ALARM technical output of collective failure –relay type, activated by:
 - 230V AC power loss
 - low voltage of the PSU (<11,5V)
 - activation of the output fuse in the camera power supply circuit
 - activation of the output fuse in the recorder power supply circuit
 - too high temperature of the PSU (>70°C)
 - the PSU failure
- protections:
 - SCP short-circuit protection
 - OVP overvoltage protection
 - overvoltage protection
 - overload protection OLP
- forced cooling (fan)
- warranty – 2 year from the production date

DESCRIPTION

The **RUPS1612RT** buffer power supply unit is designed for uninterrupted power supply of up to 16 HD cameras requiring stabilized voltage of **12V DC (+/- 15%)**. The PSU has two circuits: **1x4A/12V DC** for supplying the recorder and **16x0,75A/13,8V DC** for both cameras.

Current efficiency of the PSU amounts to:

Output current 16x0,75A + 4A recorder + 2A battery charge
Total device current + battery: 18A max.

In case of power decay, a battery back-up is activated immediately. The PSU is fitted with 16 outputs protected independently with glass fuse 1A and the output for the recorder is protected with the 4A glass fuse. The power supply is fitted with the ALARM output of collective failure. In case of failure, relay contacts are switched automatically, which is accompanied by acoustic and optical indication (the corresponding led goes on). The power supply construction is based on the switch mode PSU with high energy efficiency and is located in an enclosure adapted for mounting in standard **RACK 19"** cabinets.

RACK POWER CCTV series power supply unit

RACK mounted buffer power supply for up to 16 cameras and recorder



SPECIFICATIONS	
PSU type:	A (EPS - External Power Source)
Mains supply	176÷264V AC 50÷60Hz
Current up to	1,3A@230V AC max.
Supply power	241W max.
Efficiency	82%
Output voltage AUX1÷AUX16 - cameras	11V ÷ 13,8V DC – buffer operation 9,5V ÷ 13,8V DC – battery-assisted operation
Output voltage DVR - recorder	12V DC – maintained regardless of the state of battery charge
Output current	16 x 0,75A + 4A recorder + 2A battery charge
Ripple	120 mV p-p max.
Battery charge current (batteries 1x17Ah/ 1x28Ah/ 1x40Ah/ 1x65Ah)	2A max. (+/-5%)
Short-circuit protection SCP	cameras: 16 x F 1A, glass fuse recorder: 1 x F 4A, glass fuse
Overload protection OLP	105% ÷ 150% of the PSU power, automatic return
Overvoltage protection OVP	>16V (activation requires disconnecting the load or supply for about 20s.)
Battery circuit protection SCP and reverse polarity connection	glass fuse 30A
Surge protection	varistors
Excessive discharge protection UVP	U<9,5V (+/-5%) – disconnect of connection battery
Optical indication of operation:	LED: AC, DC, TEMP, LoB, ALARM, AUX1÷AUX16
Acoustic operation indication:	Piezoelectric indicator ~75dB/0,3m
Operating conditions	2nd environmental class, -10 °C÷ +45°C
Enclosure	Steel plate RAL 9005, black
Enclosure dimensions	W=19", H=2U; 482 x 88 x 223 mm (WxHxD)
Net weight	6,30kg / 6,70kg
Fixation	four-point butt mounting to RACK profiles – the set include 4 M6 screws + cage nuts
Declarations, warranty	CE, 2 year from the production date
Notes	Forced cooling (fan). 230V AC input: the IEC C14 socket with a fuse, power cable 2m (included) Outputs: ALARM, AUX1÷AUX16: Φ 0,5-2,1 (AWG 24-12) 0,5-1,5mm ² Output DVR: Φ 0,5-2,1 (AWG 24-12) 0,5-1,5mm ² , power cable 2m (included) Battery output BAT: 6,3F-2,5