



## Product Data Sheet

# AS374

Fire sounder, hazardous area, multi tone, horn

### General

The AS374 is a hazardous area electronic sounder for use in hazardous areas, to provide an audible warning signal in case of fire. It carries EExd IIC T4 rating, and has a marine grade aluminium housing with IP67 rating.

### Hazardous Area

The AS374 is ATEX approved with ExII 2G and EExd IIC T4 ratings. It is housed in marine grade aluminium, and offers IP67 ingress protection.

### Efficient and versatile

The AS374 provide a high sound output level, which ensures that it can be used indoor and outdoor. The AS374 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. This allows of the output level to be reduced, when the sounder is used indoors.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.



### Standard Features

- ATEX approved
- EExd IIC T4 rating
- 32 Tones user selectable
- 2nd and 3rd stage alarm
- IP67
- High output

# AS374

Fire sounder, hazardous area, multi tone, horn

## Specifications

Operation	Continuous
Supply voltage	24 VDC
Current consumption	
(see tone table in manual)	250mA typical
Sound output @ 1 metre	
(see tone table in manual)	up to 117dB(A)
Number of tones	32
Housing	Marine grade LM6 aluminium
Ingress protection	IP67
Operating temperature	-50°C to +55°C
Dimensions (Ø x D)	181 x 262 mm
Weight	3.4 Kg
Color	Red

## Ordering Information

Part No.	Description
AS374	Fire sounder, hazardous area, multi tone, horn
AS372	Fire sounder, intrinsic safe, multi tone, surface mount
FA370	Led Beacon, intrinsic safe, red lens
FA370C	Led Beacon, intrinsic safe, clear lens
FA375	5J Xenon Beacon, hazardous area, red lens
FA375Y	5J Xenon Beacon, hazardous area, yellow/amber lens

