



**UTC Fire & Security**

A United Technologies Company

## Product Data Sheet

# BS129N

Sealed Lead-Acid Battery - 12V 26Ah



### Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS129N

Sealed Lead-Acid Battery - 12V 26Ah

## Specifications

Power supply	12 VDC
Nominal capacity	26 Ah, 20 h rate
Max. charge voltage at +20°C	13.8 VDC
Max. charge current	7.8 A
Max. discharge current	130 A
Internal approx. resistance	10 mohm
Temperature	
Charge	0 to 40°C
Discharge	-15 to +50°C
Storage	-15 to +40°C
Terminal type	MS bolt & nuts
Material housing	ABS
Fire retardant	-
Weight	9.528 kg
Dimensions (W x H x D)	166 x 175 x 125 mm
VdS approval	G101079

## Ordering Information

Part No.	Description
BS129NS3	Sealed Lead-Acid Battery - 12V 26Ah - V0 Flame Retardant Case
BS129N	Sealed Lead-Acid Battery - 12V 26Ah - VdS approved

