



## Product Data Sheet

# DD1012AM

12 m volumetric Dual Technology/AM motion sensor

### Patented Range Gated Radar Technology

Motion sensors of the DD1000 Series incorporate a UTC Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.

Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.

The radar operates on 5.8GHz frequency and will not interfere with any WIFI networks.



### PIR Technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.

Within our DD1012 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

### Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.

But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

### Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

### Standard Features

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Anti-masking variant using Active Infrared and radar technology to protect against sabotage actions outside and inside of the motion sensor
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Automatic continuous self diagnostics on all technologies
- Green mode : option to switch off the radar technology when the security system is not armed
- Holding several security approvals including EN Grade III and UL/ULC

# DD1012AM

12 m volumetric Dual Technology/AM motion sensor

## Specifications

|                                    |                                           |
|------------------------------------|-------------------------------------------|
| Detection range                    | 4, 6, 9, 12 m selectable via dip switches |
| Viewing angle                      | 78°                                       |
| PIR Optics                         | 9 high density mirror curtains            |
| Microwave frequency                | 5.8 GHz                                   |
| Max. microwave output (at 1m)      | 0.003 microW/cm <sup>2</sup>              |
| Memory function                    | Yes                                       |
| Input power                        | 9 to 15 VDC (12V nominal)                 |
| Peak-to-peak ripple immunity       | 2V (at 12 VDC)                            |
| Detector start-up time             | 60 s                                      |
| Current consumption                | 10 to 20 mA (10 mA nominal)               |
| Mounting height                    | 1.8 to 3.0 m                              |
| Target speed range                 | 0.2 to 3.0 m/s                            |
| Alarm/ Tamper relay characteristic | NC, 80 mA 30 VDC, Form A                  |
| Fault relay characteristic         | NC, 80 mA 30 VDC, Form A                  |
| Alarm time                         | 3 s                                       |
| Operating temperature              | -10 to +55° C                             |
| Relative humidity                  | 95% max. non-condensing                   |
| Weight                             | 120 g                                     |
| Dimensions (H x W x D)             | 126 x 63 x 50 mm                          |
| IP/IK rating                       | IP30 IK04                                 |
| Pry-off tamper                     | On board                                  |

## Ordering Information

| Part No. | Description                                                       |
|----------|-------------------------------------------------------------------|
| DD1012AM | 12m/40ft, Dual Tech, 9C, AM                                       |
| SB01     | Wall/ceiling mount bracket (± 45° horizontal, 0° or -5° vertical) |
| AMGR2-10 | (10 PACK) Anti-mask Grade II easy wiring                          |

## Anti-masking (optical and radar)

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm is held until the effective source of the anti-masking (e.g. spray, tape,...) has been removed. Even partial masking – so going beyond the EN Grade III standard – will be detected when in advanced setting.

## Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

