



# SOC-E-IS(WHT)

## Intrinsically safe conventional smoke detector

### Description

---

The SOC-E-IS(WHT) is a WHITE, optical smoke detector designed for use in hazardous areas. It incorporates a remote indicator output and a removable chamber for easy maintenance.

The SOC-E-IS is fully compatible with the majority of current conventional systems and incorporates a unique high performance optical smoke chamber removing the need to use ionisation detectors in the majority of applications.

### Hazardous Area Classification

---

ATEX II 1G

II - Equipment group (Non-Mining)

1 - Equipment category (for Zone 0 or 20)

G - Type of explosive atmosphere (Gas, Vapours and Mist)

Cenelec Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)

Ex - Explosion protection symbol

ia - Protection concept (Intrinsically Safe)

IIC - Apparatus group (Gas)

T5 - Temperature classification (100°C)

Ga - Equipment protection level (Continuous)

Tamb - Ambient temperature range (-20 to +55°C)

### BASEEFA Certificate number

---

Bassefa 19ATEX0143X



### Details

---

- Removable, high performance chamber
- Automatic sensitivity window verification (ASWV) - Drift compensation technology
- Remote indicator output
- Wide voltage range (9.5 to 30 VDC)
- Single fire LED with 360° viewing
- Low profile design with one piece outer cover
- ATEX Classification to: Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
- Suitable for installation in areas at Category 1 (including all lower categories)
- Approved by LPCB and VdS

# SOC-E-IS(WHT)

## Intrinsically safe conventional smoke detector

### Technical specifications

---

#### General

Status indication	LED
Compatibility	Aritech, Kilsen & Ziton conventional zone interfaces using the YBN-R/4(IS) base
Connectivity	2-wire zone

#### Electrical

Power supply type	Zone powered
Operating voltage	12 to 30 VDC
Current consumption	35 $\mu$ A (quiescent) <40 mA (alarm) 120 $\mu$ A (sensitivity warning) <20 mA (remote indicator)

#### Detection

Detection principle	Optical light scatter
---------------------	-----------------------

#### Physical

Physical dimensions	100 x 48 mm ( $\varnothing$ x H)
Net weight	106 g
Colour	White
Mounting type	Base mount, Ceiling mount
Material (body)	ABS
Functional marking	BASEEFA Rating

#### Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Storage temperature	-30 to +60°C
Relative humidity	<95% noncondensing @ 40°C
Environment	Indoor, IS
Hazardous environment rating	Ex ia IIC T5 Ga (-20°C $\leq$ Ta $\leq$ +55°C)
IP rating	IP42

#### Regulatory

Compliance	CE, REACH, RoHS 2
Certification	CENELEC/ATEX, LPCB, VdS
Standards	EN54:7 IECEX BAS 19.0122X



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2023 - 9:24