

# DMN700-SW

## Conventional MCP, Flush Mount, Red, Free Contact With Glass

### General

---

The DMN700-SW is a red manual call point for flush mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 breakable glass and test key. Surface mount applications require the addition of the DM788 or DMN787.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



### Details

---

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

# DMN700-SW

## Conventional MCP, Flush Mount, Red, Free Contact With Glass

### Technical specifications

---

#### Physical

Net weight	110 g
Colour	Red

#### Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

#### Standards & regulation

Certification	EN54-11
---------------	---------

#### Cable Termination

	0.5 - 2.5 mm <sup>2</sup>
--	---------------------------

#### Max. contact rating (resistive load)

	2A @ 30 VDC
--	-------------

#### Mechanical

Material	PC/ABS
----------	--------

#### Functional marking

	Burning house
--	---------------

