

FC-178-002

Red Visual Indicator Only

General

The FC-178-002 is a RED, fire alarm Visual Indicating Device to be used with a wireless base FC-171-002.

The VID is quick and easy to install into the wireless base with a simple turn and lock mechanism.

The Range

The Fusion series consists of:

- · Optical Smoke Detectors
- · Multisensor Smoke Detectors
- · A1R Heat Detectors
- · CS Heat Detectors
- · Sounders in red and white
- · Combination Sounder VIDs and VADs
- · Manual Call Points
- · Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from is base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



Details

- For use with Fusion system
- Self-test fault monitoring
- · Individual and group addressing
- Easy to install
- Proven technology

FC-178-002 Red Visual Indicator Only

Technical specifications

General	
Wireless frequency	868 MHz
Compatibility	Wireless base FC-171-002
Electrical	
Power supply type	Batteries
Batteries	Powered by Base
Operating voltage	2.8 to 5 VDC
VID	
Colour	RED
Physical	
Physical dimensions	104 mm x 97.5 mm (Ø x H) - without base
Net weight	205 g - without base
Colour	Red
Mounting type	Base mount
Mounting base	Wireless
Environmental	
Vandal proof	No
Operating temperature	-10°C to 55°C
Storage temperature	5°C to 30°C
Relative humidity	< 95% non-condensing
Environment	Indoor
IP rating	IP54
Regulatory	
Compliancy	CE, REACH, RoHS 2, WEEE



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.