

IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Commercial Surface Mount Contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Details

- Designed for use in harsh environments
- Tamper loop
- Version with armored cable

IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Technical specifications

General

Application type	Surface Mount
Contact type	NC
Connectivity	4 wires, 2 meters (armored cable)

Wired/wireless

Wired-wireless	Wired
----------------	-------

Electrical

Cable length	2 m
Voltage	max. 40 VDC
Switching current	max. 500 mA

Physical

Physical dimensions	58 x 22 x 12 mm (W x H x D)
Colour	White
Material	ABS
Dimensions magnet	8 x 30 mm
Dimensions contact / sensor	8 x 30 mm
Operating gap	15 mm

Environmental

Operating temperature	-40° to +70° C
IP rating	IP67

Standards & regulation

EN50131 grade	Grade 3
Compliancy	CE
Certification	NFA2P

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 15 December 2020 - 12:31

