

N-IO-MBX-1

DIN Rail Module Box

General

The N-IO-MBX-1 is a surface mount enclosure designed for housing modules requiring a DIN rail mount. It's main function is to facilitate the easy installation and protection of these devices, whist keeping cabling accessible, secure and neat in the provided cable trunking inside the enclosure.



Details

- Easy installations of DIN rail mount modules on pre-fitted DIN rails
- Pre-installed cable trunking for neat cabling
- House multiple DIN units in one location in an aesthetic enclosure



Technical specifications

Physical	

Physical dimensions	377 x 417 x 110 mm (W x H x D)	
Colour	Signal white (RAL 9003)	
Material	Metal	

Environmental

Vandal proof	No	
Environment	Indoor	
IP rating	IP30	

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CE

Compatible products

Reference	Description
KE-IO3101	Intelligent addressable 1 output unit with isolator
KE-IO3101-M	Intelligent addressable mains switching output unit with isolator
KE-IO3122	Intelligent addressable 2 input / 2 output unit with isolator
KE-IO3144	Intelligent addressable 4 input / 4 output unit with isolator
rface unit KE-IU3110 Intelligent addressable 1 input unit wit isolator	
KE-IU3111-ZME	Intelligent addressable zone monitoring unit with isolator (ext. power)
	KE-IO3101 KE-IO3101-M KE-IO3122 KE-IO3144 KE-IU3110



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.