

# NC-MC-470-R

## Intelligent conventional recess mount manual call point - 470 $\Omega$ (Red)

### General

The NC-MC-470-R is a red manual call point for recess mount applications on most industry standard, high quality wall boxes. For surface mount applications an optional, colour matched back box is available.

The call point offers one normally open contact in series with a 470  $\Omega$  resistor, as well as a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 style resettable element, pluggable connectors for both contacts, a handy wire bridge to help with cable continuity testing, as well as a test key that doubles up as a service tool for disassembly of the device.

### Installation

Installation time and installation flexibility are of paramount importance. The Carrier MCP range directly meets these needs by providing features designed specifically for this. Pluggable terminal blocks facilitate the pre-connection of all cables. This terminal block is then simply connected to the MCP. Should continuity testing be needed, the handy wire bridge fits neatly into the terminal block in place of the MCP without having to disconnect any cables.

For service and maintenance no additional tools other than the test key is needed. With easy front access in all installations and even with the protection cover fitted, the test key is also used to remove the front cover of the unit should a frangible element need to be replaced.

### Options

Both break glass (frangible elements) and re-settable operating elements may be used. The MCP can be configured as either a break glass or re-settable unit by simply changing from one element to another. Other than the optional frangible element, no additional parts are required. Other parts and accessories include colour matched surface mount boxes, recess mount adapters, trim skirts, flip covers, metal test keys and replacement parts.

This range of manual call points is available in various colours with various trigger resistor options to suit most applications. In addition various function markings are available including regional language variants.



### Details

- Specifically designed for manual fire alarm activation
- Alarm indication by alarm flag and alarm LED
- Enhanced aesthetics with screen printed, high resolution functional marking
- Resettable and also usable with an optional frangible element
- Easy to install (plug and play)
- Various surface and recess mounting options available for installation flexibility
- Protection hinged cover with anti-tamper facilities available for avoiding accidental activation
- Backward compatible adapter available for retrofit applications in existing systems
- Key test facility from the front of the unit for easy access, even when a protection cover is fitted
- Easy service and maintenance with test key disassembly and pluggable connectors

# NC-MC-470-R

## Intelligent conventional recess mount manual call point - 470 $\Omega$ (Red)

### Technical specifications

---

#### General

Status indication	LED & alarm flag
Compatibility	Conventional alarm systems
Connectivity	Hardwired contacts

#### Electrical

Power supply type	Zone powered
Operating voltage	20 to 24 VDC
Current consumption	0 mA (Standby) 30 mA (Alarm)
Cable specification	0.404 - 2.05 mm $\emptyset$
No. of cable cores	2
Terminals	7

#### Detection

Detection principle	Manual activation
Monitoring	Activated, Off
Coverage area	Region specific
Zone length	< 2 km, CIE specific
Installation height	Determined by local regulation

#### Output

Output quantity	2
Output type and rating	1 x NO resistor limited, 1 x change over relay 1A @ 24 VDC

#### Physical

Physical dimensions	87 x 87 x 26 mm (W x H x D)
Net weight	101 g
Colour	Red (RAL 3028)
Mounting type	Back box, Recessed mount
Functional marking	House on Fire

#### Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-25 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP41

#### Standards & regulation

Compliance	CE, REACH, RoHS 3, WEEE
Certification	CE, CPR
Standards	EN54:11



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2022 - 15:59