



NS2052-4P-1T

4-port PoE-at and 1-port RJ45 Unmanaged Industrial Ethernet Switch

Overview

The IFS 5-port PoE Unmanaged Industrial Ethernet Switch provides four 10/100Mbps Ethernet ports with IEEE802.3-at PoE and one 10/100Mbps non-PoE Ethernet port.

This unmanaged switch provides plug-and-play installation with no programming required and is ideal for use in small IP systems. The switch uses an IP-30 standard metal case and can also be used in electrically harsh and climatically demanding environments. The switch accommodates either DIN-rail or wall mounting for efficient installation in multiple applications.

This switch is engineered with a high-performance switch architecture capable of providing a non-blocking switch fabric and wire-speed throughput of 1Gbps. With its 2K MAC address table, this switch offers wire-speed packet transfer performance without the risk of packet loss. The Flow Control function allows the switch to deliver fast and reliable IP data transfer.

This switch is ideal for applications such as IP cameras, access control, VoIP and wireless access points.

Details

- 4 RJ-45 Ports 10/100Base-TX (PoE)
- 1 RJ-45 Ports 10/100Base-TX (non-PoE)
- Store-and-Forward switching architecture with wire-speed filtering and forwarding rates
- Power over Ethernet (PoE)
- Up to 4 IEEE 802.3at devices powered
- Supports up to 30 watts for each PoE port
- Robust Hardened Design
- Provides either DIN-rail or wall-mounting
- 24 or 48VDC Operation
- Redundant power with reverse-polarity protection
- Removable terminal block for master and slave power
- Alarm relay output for power-failure alert
- Voltage/surge-suppression
- Wide operating temperature range of -40°C ~ +75°C

NS2052-4P-1T

4-port PoE-at and 1-port RJ45 Unmanaged Industrial Ethernet Switch

Technical specifications

General

Fast ring	No
DHCP snooping	No

Category

Category	Industrial
Management	Unmanaged
Managed	No
PoE	Yes

Physical ports

No. of ports	5
Port type	Fast
Speed	Fast
PoE/PoE+	4 port PoE

Switch Performance

Switch fabric	1 Gbps
Throughput (Mpps)	0.744
Mac table	2 K

Layer 2 Functions

Management interface	Unmanaged plug and play installation requires no programming
----------------------	--

Electrical

PoE power budget	30 W (per port)
Redundant power	Yes
Power supply type	24 to 48 VDC
Power consumption	77 W

Physical

Physical dimensions	56 x 88 x 135 mm
Net weight	842 g
Colour	Black
Material	Metal
Mounting type	DIN-rail, Wall mount
Stackable	No

Environmental

Operating temperature	-40 to +75
Storage temperature	-40 to 85 °C
Relative humidity	0 to 95% (non-condensing)
Environment	Indoor
IP rating	IP30

Standards & regulation

IEC standard	IEC60068-2-27 (shock), IEC60068-2-32 (free fall), IEC60068-2-6 (vibration)
Compliance	CE

LED Indicators

Power:	Power input 1 - Green; Power input 2 - Green
Power Fault:	Proper Operation - Off; Fault -Green
RJ-45 (10/100Mbps):	100Mbps Activity - Green; 10Mbps Activity - Off
Optical Link:	Link established - Steady Green; TX/RX Activity - blinking green
PoE:	PoE in use - Amber

Accessories

PS48VDC240W-EU:	100-240V AC Input 48V DC 5A Output Power Supply Hardened Brick model with EU plug
PS48VDC240W-UK:	100-240V AC Input 48V DC 5A Output Power Supply Hardened Brick model with UK plug



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 July 2021 - 10:55