Product data sheet



TVGP-M01-0401-TUR-B

TruVision 4MP, H.265+, Smart IP Turret Camera, 30 m IR, 2.8 mm lens, black

Overview

The TruVision M-series IP turret cameras leverages the latest H.265+ video compression technology to bring state of-the-art, high-definition pictures to the mass video surveillance market. With video resolutions from 2 Megapixel to 4K, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advanced technology and signal processing capability, they effectively capture video under challenging conditions.

The cameras go above and beyond standard motion detection with enhanced alarm capabilities, including cross line detection, intrusion detection and face detection features. With its smart person/vehicle feature the camera can ignore irrelevant motion or VCA events which will automatically lead to less storage consumption and faster retrieval of relevant video events.

TruVision cameras utilize H.265+ and/or H.264 compression technology with triple-streaming capability, making it easy to manage the camera's bandwidth usage. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.



Details

- Maximum resolution: 4MP (2688 x 1520)
- Person/vehicle classification
- Video intelligence: intrusion detection, cross line detection, face detection
- Up to 30 m IR illumination
- H.265+ compression
- ONVIF Profile G, S, T open standards
- Edge recording up to 256 GB SDHC card

TVGP-M01-0401-TUR-B

TruVision 4MP, H.265+, Smart IP Turret Camera, 30 m IR, 2.8 mm lens, black

Technical specifications

General	
Technology	IP
Video standard	NTSC, PAL
Image settings	Hallway View, Mirror, ROI (Region Of Interest)
Privacy masking	Yes
Software compatibility	Milestone XProtect, OnGuard, TruVision Navigator, TVRmobile, Web Browser
Camera	
Sensor size	1/3"
Max. resolution	4 MP
Sensor scan	Progressive
Sensor type	CMOS
Shutter time	1/3 to 1/100,000 s
Lighting performan	ce
WDR type	True WDR
WDR	120 dB
Digital noise reduction	3D DNR
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR
	on
Infrared (IR)	Yes
IR range	Up to 30 m
IR wavelength	850 nm
Encoding	
Video streams	3
Main stream compression	H.264, H.265, H.265+
Sub stream compression	H.264, H.265, MJPEG
Third stream compression	H.264, H.265
Video bit rate	32 to 8 Mbps
Main stream resolutions	1280 x 720 (XVGA), 1920 x 1080 (1080p), 2688 x 1520
Sub stream resolutions	640 x 360 (nHD), 640 x 480 (VGA)
Third stream resolutions	1280 x 720 (XVGA), 640 x 360 (nHD), 640 x 480 (VGA)
Max. resolution @ fps	2688 x 1520 @ 25/30 fps
Lens	
Lens type	Fixed
Focal length	2.8 mm, horizontal FoV 103°, vertical FoV 55°, diagonal FoV 122°
f-stop	F1.6
Auto iris	No


Network interface	RJ-45 10/100 Mbps self-adaptive Ethernet
Network interruce	interface
Integration	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Supported network	802.1x, Bonjour, DDNS, DHCP, DNS, FTP, HTTP,
protocols	HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTCP, RTP, RTSP, SMTP, SNMP, TCP/IP, UPnP
Storage	
Local storage type	Built-in Micro SD/SDHC/SDXC card slot
Max. SD card capacity	256 GB
Video intelligence	
Alarm trigger	HDD error, HDD full, Invalid login, IP address
	conflict, Motion detection, Network
	disconnected, Video tampering
ROI	Support 1 fixed region for main stream and substream $% \left(1\right) =\left(1\right) \left(1\right) $
Video analytics	Advanced motion detection, Face detection,
	Intrusion detection, Line crossing detection,
	Motion detection
Intelligence options	Person/vehicle detection on motion, line crossing and intrusion detection
Electrical	
Operating voltage	12 VDC, 0.5 A, PoE (802.3af, 36 to 57 V), 0.19 to 0.12 A
Power consumption	max. 7 W
Physical	
Physical dimensions	Ø127.3 × 95.9 mm
	Ø5.01 × 3.78 in.
Net weight	600 g
	1.3 lb.
Shipping weight	816 g
	1.8 lb.
Colour	Black
Material Form Factor	Aluminium Turret
	Turret
Environmental	
Environment	Outdoor
Operating temperature	-30 to +60°C -22 to +140°F
Relative humidity	<95% noncondensing
IP rating	IP67
Regulatory	
Compliancy	CE, FCC, REACH, RoHS, UL, WEEE
	·

TVGP-M01-0401-TUR-B

TruVision 4MP, H.265+, Smart IP Turret Camera, 30 m IR, 2.8 mm lens, black







Unit: mm



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.