

TVN-1204C-1T

TruVision NVR 12, 4 channels, 40 Mbps, 1 TB

Reasons for choosing TVN 12

The TVN 12c recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP (4K). The TVN-1204c is a cost-effective, easy-to-use recorder capable of recording up to four IP cameras.

Ease to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.

The TVN 12c can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.

In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

Applications

The TVN 12c is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.



Details

- Linux embedded Plug and Play configuration
- Supports H.264, H.265 and H.265+ encoding, depending on the cameras
- Up to 40 Mbps camera recording bandwidth
- Up to four IP channels with a maximum resolution of 4K (8 MP)
- 1 TB embedded storage
- Real time recording (Up to 4 MP)
- HDMI/VGA monitor output
- TruVision IP camera auto-detection
- IP camera configuration import/export
- UltraSync support for remote access without port forwarding
- Motion detection, VCA, privacy masking and tamper detection
- Dedicated people/vehicle detection in combination with supported cameras
- Third party camera support via ONVIF Profile S or RTSP (custom protocols)
- Integration of Carrier IP intrusion panels via SIA/XSIA reporting
- TVK-600 IP keypad support
- USB DVD burner support
- Full browser-, OSD- and software-based access for live, recorded video
 & configuration
- TVRMobile app for iOS and Android for remote viewing
- TruVision Navigator license-free client/host or standalone application support
- External integration through SDK

TVN-1204C-1T

TruVision NVR 12, 4 channels, 40 Mbps, 1 TB

Technical specifications

General	
Technology	IP
Operating system	Embedded Linux
Rack mountable	No
Video / audio input	
Camera channels	4
IP camera channels	4
Camera bandwidth	40 Mbps
Audio compression	G.711alaw, G.711ulaw, G.722, G.726
Max. IP audio in	4
Max. analog audio In	1
Supported video	H.264, H.265, H.265+
compression standards	
Supported video	Onvif, RTSP Custom Protocols
streaming standards	
Local viewing	
HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output	4K
resolution	
Synchronous playback OSD (channels)	Up to 4 channels (1080P)
Remote viewing	
Total available viewing	80 Mbps
bandwidth	
Max. live viewing	128 streams
streams	
Max. playback viewing streams	Max. 8 streams
Max. simultaneous	Up to 8 channels
playback web browser	•
Reverse playback web browser (channels)	Up to 8 channels
Software compatibility	Advisor Management Software (ATS8600) TruVision Navigator, TVRmobile
Browser compatibility	Google Chrome, Internet Explorer, Mozilla
	Firefox, Safari
Storage	
Storage capacity	1 TB
SATA interfaces	1
Max. capacity per SATA HDD (TB)	8
Maximum recording	4 K
resolution	
Recording modes	Continuous, Event, Manual
External storage	NAS
Edge failover recording	Yes

Networking	
Network interface cards (NIC)	1
NIC type	RJ-45 10/100 Mbps self-adaptive Ethernet interface
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	Yes
External interfaces	
USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1
Electrical	
Power supply type	12 VDC
Power consumption without HDD (W)	≤10 W
Physical	
Physical dimensions	320 x 240 x 48 mm (W x D x H)
Net weight	1.1 kg
Colour	Black
Environmental	
Operating temperature	-10 to +55°C
Relative humidity	10 to 90% noncondensing

CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Regulatory Compliancy