

TVN-1208-4T TruVision NVR 12, 8 channels, 80 Mbps, 4 TB

Why the TVN 12?

The TVN 12 recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP(4K). The TVN-1208 is a cost-effective, easy-to-use recorder capable of recording up to eight IP cameras.

Easy to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.

The TVN 12 can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.

In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

Applications

The TVN 12 is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.



Details

- Linux embedded Plug and Play configuration
- Supports H.264, H.265 and H.265+ encoding, depending on the cameras
- Up to 80 Mbps camera recording bandwidth
- Up to eight IP channels with a maximum resolution of 4K (8 MP)
- 4 TB embedded storage
- Real time recording (Up to 4 MP)
- Dual stream recording, configurable per camera
- HDMI/VGA monitor output
- TruVision IP camera auto-detection
- IP camera configuration import/export
- UltraSync support for remote access without port forwarding
- · Motion detection and VCA support, depending on the cameras
- Dedicated people/vehicle detection in combination with supported cameras
- Third party camera support via ONVIF Profile S or RTSP (custom protocols
- Integration of Carrier IP intrusion panels via SIA/XSIA reporting
- TVK-600 IP keypad support
- USB DVD burner support
- Full browser-, OSD- and software-based access for live, recorded video & configuration
- TVRMobile app for iOS and Android for remote viewing
- TruVision Navigator client/host or standalone application support
- External integration through SDK

TVN-1208-4T TruVision NVR 12, 8 channels, 80 Mbps, 4 TB

Technical specifications

General	
Technology	IP
Operating system	Embedded Linux
Rack mountable	Yes
Rack stacking size	1 U
Video/audio input	
Camera channels	8
IP camera channels	8
Camera bandwidth	80 Mbps
Audio compression	G.711alaw, G.711ulaw, G.722, G.726
Max. IP audio in	8
Max. analog audio In	1
Supported video	H.264, H.265, H.265+
compression standards	
Supported video	Onvif, RTSP Custom Protocols
streaming standards	

Local viewing

HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output resolution	4К
Synchronous playback OSD (channels)	Up to 8 channels (1080P)

Remote viewing

Maximum recording

Dual stream recording

Edge failover recording

resolution Recording modes

(channels) External storage

0	
Total available viewing bandwidth	80 Mbps
Max. live viewing streams	128 streams
Max. playback viewing streams	16 streams
Max. simultaneous playback web browser	Up to 16 channels
Reverse playback web browser (channels)	Up to 16 channels
Software compatibility	Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari
Storage	
Storage capacity	4 TB
SATA interfaces	2
Max. capacity per SATA HDD (TB)	8

Continuous, Event, Manual

(NIC) NIC type RJ-45 10/100 Mbps self-adaptive Ethernet interface DNS support DDNS, ezDDNS, No-IP HTTPS support Yes **External interfaces** USB interface back 1 USB interface front 1 Alarm inputs 4 Alarm outputs 1 Max. analog audio 1 outputs **Electrical** Power supply type 12 VDC Power consumption 15 W without HDD (W) **Physical** Physical dimensions 385 x 315 x 52 mm (W x D x H) Net weight 1.7 kg Colour Black **Environmental** Operating temperature -10 to +55 °C Relative humidity 10 to 90% noncondensing Regulatory Compliancy CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE

Networking

Network interface cards 1



4 K

NAS

Yes

8 channels

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.