



## DF160

FlexZone-60 processor in NEMA aluminum enclosure

FlexZone processor (DF160) gives advanced warning of unwanted intrusions at the perimeter and is easily installed on most fences by attaching its lightweight sensor cable to the fence fabric with cable ties. The DF160 processor provides up to 60 independent zones of detection and comes in an outdoor rated enclosure, which can be easily post mounted or fixed to any convenient supporting surface.

Each FlexZone processor provides connection for two sensor cables that can be up to 600 m long and act independently to provide two distinct detection zones. All configuration and detection parameters for each zone are set using the Windows-based Universal Configuration Module software (DF950-CM).

FlexPS processors can communicate alarm and system status by relay outputs or optionally over a data communications network to a remote security management system. Unlike a block sensor, where all events are aggregated together along the entire zone length (including ones caused by distributed environmental conditions), FlexZone divides the events into precise, localized areas, thus maximizing the probability of detection while reducing nuisance alarms.



### Standard Features

- Sensor processing capability up to 600 m of active sensor cable
- Adaptive Algorithms virtually eliminate environmental nuisance alarms
- Configurable with laptop PC via direct USB connection or over the sensor network
- Built in audio module
- Detection parameters can be set and optimized independently for each zone
- Built in relays; optional network communication cards
- IP66, NEMA Type 4X enclosure

# DF160

## FlexZone-60 processor in NEMA aluminum enclosure

### Specifications

Power input	12 to 60 VDC
Current consumption	2 W nominal; 2.5 W nominal with network interface card
Power over sensor cables	48V, 50 W power supply required
Power supply sharing	Up to 5 processors per power supply
Enclosure	IP66 / NEMA 4 painted aluminum, outdoor rated
Maximum sensor cable length	600m max; zone length app. 10% less @ 540 m.
Operating temperature	-40 to +70°C
Relative humidity	100% condensing
Controls	calibration adjustments via the Universal Configuration Module (Windows-based software application)
Inputs	2 sensor cable inputs (1 per cable side)
Outputs	4 form C relay outputs 30 VDC @ 1 A maximum, noninductive load user-configurable relay response
Dimensions	31.6 cm x 18.6 cm x 9 cm
Weight	1.2 kg

### Ordering Information

Part No.	Description
DF160	FlexZone-60 processor in NEMA aluminum enclosure

