



DF420

Wireless gate sensor module, solar-powered, gray enclosure

Operation

The E-Flex 3i signal processor monitors and analyzes either of two selectable frequency bands, and produces an alarm when the signals, generated by the E-Flex sensor cable, exceed the threshold for the selected band. In addition to selecting the proper frequency response, the user can select the number of impacts required before an alarm is generated; the length of time during which those impacts must occur; and the minimum duration of a sustained attack required to generate an alarm. Since all materials have different responses to a penetration attack, the E-Flex 3i can be calibrated to provide optimum performance for each application. Total sensor sensitivity is adjustable to any of ten discreet levels.



Standard Features

- 300 m transmission range with the supplied rubber whip antenna
- Secure RF transmissions via 128-bit encryption
- Supervised comm link
- Supervised input for auxiliary device alarm reporting
- Solar powered- requires 2 hrs indirect sunlight per day (nomila) 5 days run time with no light (from fully charged)

DF420

Wireless gate sensor module, solar-powered, gray enclosure

Ordering Information

Part No.	Description
DF420	Wireless gate sensor module, solar-powered, gray enclosure
DF811	Sensor Cable 300 m
DF811S150	
DF813	
DF821	Self-adhesive Clips - 500 pcs for Indoors
DF823	Cable Splice / Terminator Kit
DF824	

