



Product Data Sheet

DM863-0

MCP WHITE, Gas Extinguishing Abort, 100 ohm, English, Dutch & French

General


The DM863-0 is a Type B / Dual action manual call point for surface mount applications. It is specifically designed for use with the FEC403EN gas extinguishing panel, and includes language inserts for English, Dutch & French.

Construction

The rugged aluminum housing, combined with a fade resistant coating guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass. The revolving door also contains a special clip, which features as a failsafe, to prevent the door from being closed while the unit is still triggered.

Dual action

The DM863-0 is defined as a type B /dual action manual call point, due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.



Standard Features

- Robust aluminium housing
- Type B / Dual action
- Surface mount

DM863-0

MCP WHITE, Gas Extinguishing Abort, 100 ohm, English, Dutch & French

Specifications

Series resistor	100 ohm
Housing	Aluminum
Dimensions	125 x 125 x 34 mm
Weight	400g
Color	White
Operating Temperature	-20°C to +60°C
IP Rating	IP43

Ordering Information

Part No.	Description
DM863-0	MCP WHITE, Gas Extinguishing Abort, 100 ohm, English, Dutch & French
DM966	Replacement CLEAR Windows for Push-button-activated Manual Call Points
DM861-0	MCP YELLOW, Gas Manual Release, 100 ohm, English, Dutch & French
DM862-0	MCP BLUE, Gas Extinguishing Hold, 100 ohm, English, Dutch & French
DM861-4	MCP YELLOW, Gas Manual Release, 100 ohm, Spanish, Portuguese & Italian
DM862-4	MCP BLUE, Gas Extinguishing Hold, 100 ohm, Spanish, Portuguese & Italian
DM863-4	MCP WHITE, Gas Extinguishing Abort, 100 ohm, Spanish, Portuguese & Italian
DM865	MCP RED, Manual Fire Alarm, 100 ohm

