

## **Product Data Sheet**

# **DMN700G**

Manual callpoint, flush mount, green, free contact, break glass

#### General

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP indoor call point range.

#### Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.



Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



#### Standard Features

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatibale
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

# **DMN700G**

Manual callpoint, flush mount, green, free contact, break glass

### **Specifications**

Cable Termination	0.5 - 2.5 mm²
Max. contact rating (resistive load)	2A @ 30 VDC
Mechanical	
Material	PC/ABS
Weight	110g
Colour	Green
Environmental	
Operating temperature	-10°C to +55°C
Storage temperature	-10°C to +55°C
Relative humidity (non-condensing)	0-95%
IP Rating	IP24D

## **Ordering Information**

Part No.	Description
DMN700G	Manual callpoint, flush mount, green, free contact, break glass
DMN787G DM788GR DM711 DM715 DMN782 DMN784	Surface mounting box with earth connector, green Surface mount box without connectors, green EN54 universal glass ARITECH branded EN54 Universal MCP Glass (without branding) Hinged transparent MCP protection cover Call Point Test Key
DMN798 DMN800	Breakable Seal for Manual Call Points Resettable Element for Manual Call Point

