



Product Data Sheet

FE160US

Eco Line magnetic lock 600 kgf, unmonitored, surface mount

Description

Eco Line single magnetic lock, 600 kgf. Surface mounting unmonitored.

Application

High security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Standard Features

- 600 kgf holding power
- Surface mount
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Unmonitored
- Mounts easily with a minimum of tools

FE160US

Eco Line magnetic lock 600 kgf, unmonitored, surface mount

Specifications

Mount	Surface
Holding force	600 kgf
Input voltage	12/24 VDC
Current draw	430 mA (+/- 2,5% @ 13,5 V)
Dimensions (W x H x D)	266 x 73 x 40 mm
Bi colour LED	No
Door status switch	No
Monitored changeover	No
Magnetic bond sensor	No

Ordering Information

Part No.	Description
FE160US	Eco Line magnetic lock 600 kgf, unmonitored, surface mount

