



## Product Data Sheet

# GS302

Piezo glassbreak detector 20 m

### High Performance

The glassbreak detector GS302 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm.

Suitable for use on standard window glass or plate glass the GS302 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass.

The detector is moulded into a plastic housing and delivered with 20m cable. They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



### Características Standard

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

# GS302

Piezo glassbreak detector 20 m

## Especificações Técnicas

Power supply	3 to 16 V
Max. ripple	1 V
Current draw	
Normal	about 4mA at 6V
Alarm	9 mA at 12 VDC
Alarm output	N/A
Tamper	Protected against cutting the cable
Operating temperature	-25 to +70°C
Detection range	2 m radius
Dimensions	37 x 19 x 12 mm
Weight	50 g
Cable length	20 m
IP rating	IP67

## Como Encomendar

Referência	Descrição
GS302	Piezo glassbreak detector 20 m

