



Product Data Sheet

PB10

1m - 180° AIR Beam Tower (single sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 1 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP3)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 8 pcs (EP3) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 1 pcs (EP3)
15. Cable gland PGM20 : 1 pcs (EP3)
16. M8x16 DIN933 : 4 pcs (TA3)
17. Side bracket <2m : 2 pcs
18. M8 DIN 985 : 4 pcs (TA3)
19. M8 DIN 125 : 4 pcs (TA3)
20. M4x12 DIN 7985 : 4 pcs (C3)
21. Bracket : 2 pcs
22. dia.2.9x16 DIN 7981 : 4 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2)



Standard Features

- 1.00m height
- 180° view
- CE certified product

PB10

1m - 180° AIR Beam Tower (single sided) including installation kit.

Specifications

Voltage	12 to 24 VDC
Angle of view	180°
Tamper switch output	CO (change over)
Operating temperature	-15 to +50°C
Material	Aluminium, plastic (polycarbonate, ABS)
Dimensions (HxWxD)	97 x 13 x 15cm
Weight	2.95kg

Ordering Information

Part No.	Description
BS121N	Sealed Lead-Acid Battery - 12V 1.2Ah - VdS approved
PB10	1m - 180° AIR Beam Tower (single sided) including installation kit.
PB20-SB	Spare side brackets for 1-2m pillars
PB34	Stainless wire set for installation of pillars in extreme wind conditions
PB50-AC180	Anti climb top tamper for 180° beam towers
PB50-FB	Floor bracket for concrete (difficult grounds) for 180° and 360° beam towers
PB50-WB	Wall bracket for 180° beam tower
PB51	Bracket kit for mounting beam, power supply or battery for PB pillars (pack of 2)
SB52	Power Supply 230VAC to 12VAC & 12VDC
PB50-H	12V non polarity heater 250mA for beam tower
PB50-T	Thermostat for beam tower

